

OIL THERMOREGULATORS



NO L



PROFILE

The NO /L series oil thermoregulators have been studied for the heating and the 150 °C thermoregulation of moulds and cylinders with operating temperatures up to. They are used in several industrial fields such as those of plastic, rubber, die-casting and all those fields needing the control of high temperatures. These products ensure the user an even temperature with a completely automatic operation thanks to the use of instruments technologically in the lead. The set-point is reached with a constant auto-tuning action, which regulates the power supplied, adjusting it to the external load conditions.

The accrued design allowed to obtain, the best stability of the set temperature as well as absence of thermal fluctuations resulting in a considerable energy saving. Such result may be achieved thanks to the use of special, modulating valves and exchangers with a wide exchange surface which, with their combined action, let temperature quickly and precisely reach the set-point value.

The oil version, thanks to its particular design, aided by the use of special diathermic oil can work non-stop at the highest temperature without spoiling the fluid. All our thermoregulators may be coupled in series with a chiller, in this case we get a closed, cooling circuit with no water consumption.

OIL THERMOREGULATORS

TECHNICAL DATA

Model (1)	Type of fluid	Max temp.	Electrical heaters		Commutations		Pump			Type of cooling	Total capacity
			n°	kW	n°	kW	kW	l/min	bar		
		°C	n°	kW	n°	kW	kW	l/min	bar		l
NO 03 L	oil	150	1	3,0	1	3	3,8	60	9,0 - 0,5	indirect	20
NO 06 L	oil	150	1	6,0	1	6	3,8	60	9,0 - 1,0	indirect	20
NO 09 L	oil	150	1	9,0	1	9	3,8	60	9,0 - 1,0	indirect	20

(1) - Standard electric alimention 400V-3Ph-50Hz - Special on request

DIMENSIONS AND WEIGHTS

Model	Dimensions			Net weight	Sound Level (2)
	L mm	P mm	H mm		
NO 03 L	650	300	590	50	55
NO 06 L	650	300	590	50	55
NO 09 L	650	300	590	50	55

(2) - Sound pressure level at 10 metres



NOVA FRIGO Engineering S.r.l.

Via Montebello, 5/D
25017 - LONATO (BS) - ITALIA
Tel: (+39) 030 99 13 250
Fax: (+39) 030 99 19 043
e-mail: info@novafrigo.it
www.novafrigo.it